

## OKY3330

**Product Name: MQ-5 Combustible Gas Propane/Butane Detector Sensor Module**

**Product Module:** OKY3330

### Quick Details:

- \*Indication of the signal output.
- \* Dual signal output (analog output, and TTL level output)
- \*TTL output signal is low. (When low output signal light, and can be connected directly to the microcontroller)
- \*0 ~ 5V analog output voltage, the higher the concentration, the higher the voltage.
- \*Liquefied petroleum gas, natural gas, city gas, better sensitivity.
- \*Has a long life and reliable stability
- \*Fast response and recovery characteristics
- \*Excellent resistance to alcohol, smoke interference ability.

### Product Description:

The heating voltage : 5 + 0.2V (AC . DC)  
Working current : 150mA  
The circuit voltage : 0 DC15V ( Max DC15V)  
The load resistance : 1K ( adjustable )  
The test concentration range :300-5000ppm  
Clean air voltage : < 1.5V  
Sensitivity :  $\geq 3\%$   
Response time : < 1S ( preheat 30-50 minutes )  
Response time : < 30S  
The component power consumption : < 0.9W  
Working temperature : -10 ~ 50 oC ( nominal temperature 20 oC)  
Humidity : 95% RH ( nominal humidity 65% RH)

### Package Included

1PCS X MQ-5 Combustible Gas Propane/Butane Detector Sensor Module

